



GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: GLOW AQUA Fluorescent Acrylic Paint - Purple

Other means of identification:

Not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Decorative paint

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

SPLinx Jacek Bisiorek

Kościelna 1

05-126 Kąty Węgielskie - mazowieckie - Polska

Phone: +48 604 591 256

jbisiorek@splinx.pl

www.splinx.pl

1.4 Emergency telephone number: 112; SPLinx: +48 604 591 256

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P273: Avoid release to the environment.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

Supplementary information:

EUH208: Contains C.I.Basic Red 1:1, Formaldehyde, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione. May produce an allergic reaction.

EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Substances that contribute to the classification

1,2-benzisothiazol-3(2H)-one (CAS: 2634-33-5); Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione (CAS: 5395-50-6); Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (CAS: 55965-84-9); 2-methylisothiazol-3(2H)-one (CAS: 2682-20-4); C.I.Basic Red 1:1 (CAS: 3068-39-1); Formaldehyde (CAS: 50-00-0)

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

- CONTINUED ON NEXT PAGE -



GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 14807-96-6 EC: 238-877-9 Index: Non-applicable REACH: Non-applicable	Tak not containing mineral fibres (incl. asbestos)⁽¹⁾ Regulation 1272/2008	Not classified	1 - <2,5 %
CAS: 5395-50-6 EC: 226-408-0 Index: Non-applicable REACH: 01-2120762062-63-XXXX	Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione⁽²⁾ Regulation 1272/2008	Skin Sens. 1B: H317 - Warning	<1 %
CAS: 131-57-7 EC: 205-031-5 Index: Non-applicable REACH: 01-2119976330-39-XXXX	2-hydroxy-4-methoxybenzophenone⁽²⁾ Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 2: H411 - Warning	<1 %
CAS: 3068-39-1 EC: 221-326-1 Index: Non-applicable REACH: 01-2120107344-68-XXXX	C.I.Basic Red 1:1⁽²⁾ Regulation 1272/2008	Self-classified Acute Tox. 1: H330; Acute Tox. 4: H302; Eye Dam. 1: H318; Skin Sens. 1B: H317 - Danger	<1 %
CAS: 34590-94-8 EC: 252-104-2 Index: Non-applicable REACH: 01-2119450011-60-XXXX	Dipropylene Glycol Methyl Ether⁽³⁾ Regulation 1272/2008	Not classified	<1 %
CAS: 50-00-0 EC: 200-001-8 Index: 605-001-00-5 REACH: 01-2119488953-20-XXXX	Formaldehyde⁽²⁾ Regulation 1272/2008	Self-classified Acute Tox. 2: H330; Acute Tox. 3: H301+H311; Carc. 1B: H350; Skin Corr. 1B: H314; Skin Sens. 1A: H317 - Danger	<1 %
CAS: 55965-84-9 EC: Non-applicable Index: 613-167-00-5 REACH: Non-applicable	Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)⁽²⁾ Regulation 1272/2008	ATP ATP13 Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger	<1 %

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽³⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	M-factor	
C.I.Basic Red 1:1	Acute	10
CAS: 3068-39-1 EC: 221-326-1	Chronic	1
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Acute	100
CAS: 55965-84-9 EC: Non-applicable	Chronic	100

Identification	Specific concentration limit
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	% (w/w) >=0,6: Skin Corr. 1C - H314
CAS: 55965-84-9	0,06< % (w/w) <0,6: Skin Irrit. 2 - H315
EC: Non-applicable	% (w/w) >=0,6: Eye Dam. 1 - H318
	0,06< % (w/w) <0,6: Eye Irrit. 2 - H319
	% (w/w) >=0,0015: Skin Sens. 1A - H317

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
C.I.Basic Red 1:1 CAS: 3068-39-1 EC: 221-326-1	LD50 oral	449 mg/kg	Rat
	LD50 dermal	Not relevant	
	LC50 inhalation	0,05 mg/L (ATEI)	
Formaldehyde CAS: 50-00-0 EC: 200-001-8	LD50 oral	100 mg/kg	Rat
	LD50 dermal	270 mg/kg	Rabbit
	LC50 inhalation	Not relevant	

- CONTINUED ON NEXT PAGE -



GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Acute toxicity		Genus
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable	LD50 oral	64 mg/kg	Rat
	LD50 dermal	87,12 mg/kg	Rabbit
	LC50 inhalation	Not relevant	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

- CONTINUED ON NEXT PAGE -



GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 25 °C

Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

- CONTINUED ON NEXT PAGE -



GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits		
Dipropylene Glycol Methyl Ether ⁽¹⁾	IOELV (8h)	50 ppm	308 mg/m ³	
CAS: 34590-94-8	IOELV (STEL)			
Formaldehyde ⁽²⁾	IOELV (8h)	0,3 ppm	0,37 mg/m ³	
CAS: 50-00-0	IOELV (STEL)	0,6 ppm	0,74 mg/m ³	

⁽¹⁾ Skin

⁽²⁾ Dermal sensitisation

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Tak not containing mineral fibres (incl. asbestos) CAS: 14807-96-6 EC: 238-877-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	43,2 mg/kg	Not relevant
	Inhalation	2,16 mg/m ³	3,6 mg/m ³	2,16 mg/m ³	3,6 mg/m ³
2-hydroxy-4-methoxybenzophenone CAS: 131-57-7 EC: 205-031-5	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	39 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	27,7 mg/m ³	Not relevant
C.I. Basic Red 1:1 CAS: 3068-39-1 EC: 221-326-1	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	0,06 mg/kg	Not relevant	0,02 mg/kg	Not relevant
	Inhalation	0,2 mg/m ³	Not relevant	0,06 mg/m ³	Not relevant
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	283 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	308 mg/m ³	Not relevant
Formaldehyde CAS: 50-00-0 EC: 200-001-8	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	240 mg/kg	Not relevant
	Inhalation	Not relevant	0,75 mg/m ³	9 mg/m ³	0,375 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Tak not containing mineral fibres (incl. asbestos) CAS: 14807-96-6 EC: 238-877-9	Oral	160 mg/kg	Not relevant	160 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	21,6 mg/kg	Not relevant
	Inhalation	1,08 mg/m ³	1,8 mg/m ³	1,08 mg/m ³	1,8 mg/m ³
2-hydroxy-4-methoxybenzophenone CAS: 131-57-7 EC: 205-031-5	Oral	Not relevant	Not relevant	2 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	20 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	6,8 mg/m ³	Not relevant
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Not relevant	Not relevant	36 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	121 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	37,2 mg/m ³	Not relevant
Formaldehyde CAS: 50-00-0 EC: 200-001-8	Oral	Not relevant	Not relevant	4,1 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	102 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	3,2 mg/m ³	0,1 mg/m ³

PNEC:

Identification				
Tak not containing mineral fibres (incl. asbestos) CAS: 14807-96-6 EC: 238-877-9	STP	Not relevant	Fresh water	597,97 mg/L
	Soil	Not relevant	Marine water	141,26 mg/L
	Intermittent	597,97 mg/L	Sediment (Fresh water)	31,33 mg/kg
	Oral	Not relevant	Sediment (Marine water)	3,13 mg/kg
2-hydroxy-4-methoxybenzophenone CAS: 131-57-7 EC: 205-031-5	STP	10 mg/L	Fresh water	0,00067 mg/L
	Soil	0,013 mg/kg	Marine water	0,000067 mg/L
	Intermittent	0,0067 mg/L	Sediment (Fresh water)	0,066 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,007 mg/kg

- CONTINUED ON NEXT PAGE -

GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification					
C.I. Basic Red 1:1 CAS: 3068-39-1 EC: 221-326-1	STP	0,33 mg/L	Fresh water	0 mg/L	
	Soil	0,198 mg/kg	Marine water	0 mg/L	
	Intermittent	0 mg/L	Sediment (Fresh water)	0,989 mg/kg	
	Oral	0,0001 g/kg	Sediment (Marine water)	0,099 mg/kg	
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	STP	4168 mg/L	Fresh water	19 mg/L	
	Soil	2,74 mg/kg	Marine water	1,9 mg/L	
	Intermittent	190 mg/L	Sediment (Fresh water)	70,2 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	7,02 mg/kg	
Formaldehyde CAS: 50-00-0 EC: 200-001-8	STP	0,19 mg/L	Fresh water	0,44 mg/L	
	Soil	0,2 mg/kg	Marine water	0,44 mg/L	
	Intermittent	4,44 mg/L	Sediment (Fresh water)	2,3 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	2,3 mg/kg	

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	 CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	 CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	 CAT I		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	 CAT II	EN ISO 20347:2022	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2022 y EN 13832-1:2007

F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -

GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011		DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0,1 % weight
V.O.C. density at 20 °C:	1,13 kg/m³ (1,13 g/L)
Average carbon number:	7
Average molecular weight:	148,15 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Characteristic
Colour:	 Violet
Odour:	Not available
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	100 °C
Vapour pressure at 20 °C:	2166 Pa
Vapour pressure at 50 °C:	11416,77 Pa (11,42 kPa)
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	1139,6 kg/m³
Relative density at 20 °C:	1,14
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

Flammability:

Flash Point:	>100 °C
--------------	---------

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Flammability (solid, gas):	Not relevant *
Autoignition temperature:	270 °C
Lower flammability limit:	Not relevant *
Upper flammability limit:	Not relevant *
Particle characteristics:	

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- CONTINUED ON NEXT PAGE -



GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
IARC: Titanium oxide (2B); Tak not containing mineral fibres (incl. asbestos) (3); Formaldehyde (1)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
C.I.Basic Red 1:1 CAS: 3068-39-1 EC: 221-326-1	LD50 oral	449 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation	0,05 mg/L (ATEI)	
2-hydroxy-4-methoxybenzophenone CAS: 131-57-7 EC: 205-031-5	LD50 oral	12800 mg/kg	Rat
	LD50 dermal	16000 mg/kg	Rat
	LC50 inhalation		
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	9510 mg/kg	Rabbit
	LC50 inhalation		

- CONTINUED ON NEXT PAGE -



GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
Formaldehyde CAS: 50-00-0 EC: 200-001-8	LD50 oral	100 mg/kg	Rat
	LD50 dermal	270 mg/kg	Rabbit
	LC50 inhalation	1,1 mg/L (4 h)	Rat
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable	LD50 oral	64 mg/kg	Rat
	LD50 dermal	87,12 mg/kg	Rabbit
	LC50 inhalation	0,33 mg/L (4 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Tak not containing mineral fibres (incl. asbestos) CAS: 14807-96-6 EC: 238-877-9	LC50	100000 mg/L (24 h)	Brachydanio rerio	Fish
	EC50	Not relevant		
	EC50	Not relevant		
2-hydroxy-4-methoxybenzophenone CAS: 131-57-7 EC: 205-031-5	LC50	3,8 mg/L (96 h)	Oryzias latipes	Fish
	EC50	1,87 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	0,72 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LC50	10000 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1919 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Not relevant		
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable	LC50	0,28 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	0,16 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	0,018 mg/L (72 h)	Selenastrum capricornutum	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
Tak not containing mineral fibres (incl. asbestos) CAS: 14807-96-6 EC: 238-877-9	NOEC	5979,718 mg/L	N/A	Fish
	NOEC	1459,798 mg/L	N/A	Crustacean
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	NOEC	Not relevant		
	NOEC	0,5 mg/L	Daphnia magna	Crustacean
Formaldehyde CAS: 50-00-0 EC: 200-001-8	NOEC	Not relevant		
	NOEC	6,4 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
2-hydroxy-4-methoxybenzophenone CAS: 131-57-7 EC: 205-031-5	BOD5	Not relevant	Concentration	100 mg/L
	COD	2,2 g O2/g	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	65 %
C.I.Basic Red 1:1 CAS: 3068-39-1 EC: 221-326-1	BOD5	Not relevant	Concentration	17 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	2 %

- CONTINUED ON NEXT PAGE -



GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	BOD5	Not relevant	Concentration	Not relevant
	COD	0 g O ₂ /g	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	73 %
Formaldehyde CAS: 50-00-0 EC: 200-001-8	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	92 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
2-hydroxy-4-methoxybenzophenone CAS: 131-57-7 EC: 205-031-5	BCF	160
	Pow Log	3.45
	Potential	High
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	BCF	1
	Pow Log	-0.06
	Potential	Low
Formaldehyde CAS: 50-00-0 EC: 200-001-8	BCF	3
	Pow Log	0.35
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
2-hydroxy-4-methoxybenzophenone CAS: 131-57-7 EC: 205-031-5	Koc	955	Henry	1,52E-3 Pa·m ³ /mol
	Conclusion	Low	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP6 Acute Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

- CONTINUED ON NEXT PAGE -

GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 14: TRANSPORT INFORMATION (continued)

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

14.1 UN number or ID number:	Not relevant
14.2 UN proper shipping name:	Not relevant
14.3 Transport hazard class(es):	Not relevant
Labels:	Not relevant
14.4 Packing group:	Not relevant
14.5 Environmental hazards:	No
14.6 Special precautions for user	
Special regulations:	Not relevant
Tunnel restriction code:	Not relevant
Physico-Chemical properties:	see section 9
Limited quantities:	Not relevant
14.7 Maritime transport in bulk according to IMO instruments:	Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



14.1 UN number or ID number:	UN2810
14.2 UN proper shipping name:	TOXIC LIQUID, ORGANIC, N.O.S. (Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1))
14.3 Transport hazard class(es):	6.1
Labels:	6.1
14.4 Packing group:	III
14.5 Marine pollutant:	No
14.6 Special precautions for user	
Special regulations:	274, 223
EmS Codes:	F-A, S-A
Physico-Chemical properties:	see section 9
Limited quantities:	5 L
Segregation group:	Not relevant
14.7 Maritime transport in bulk according to IMO instruments:	Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



14.1 UN number or ID number:	UN2810
14.2 UN proper shipping name:	TOXIC LIQUID, ORGANIC, N.O.S. (Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1))
14.3 Transport hazard class(es):	6.1
Labels:	6.1
14.4 Packing group:	III
14.5 Environmental hazards:	No
14.6 Special precautions for user	
Physico-Chemical properties:	see section 9
14.7 Maritime transport in bulk according to IMO instruments:	Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- CONTINUED ON NEXT PAGE -



GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 15: REGULATORY INFORMATION (continued)

- Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 1,2-benzisothiazol-3(2H)-one, Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione, Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 2-methylisothiazol-3(2H)-one.
- Article 95, REGULATION (EU) No 528/2012:
Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione (5395-50-6) - PT: (6,11,12,13) ; Formaldehyde (50-00-0) - PT: (2,3,22) ; Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9) - PT: (2,4,6,11,12,13)
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Not relevant

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Not relevant

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 1: H330 - Fatal if inhaled.

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.

Acute Tox. 2: H330 - Fatal if inhaled.

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin.

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Carc. 1B: H350 - May cause cancer.

Eye Dam. 1: H318 - Causes serious eye damage.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

GLOW AQUA Fluorescent Acrylic Paint - Purple

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

SECTION 16: OTHER INFORMATION (continued)

Classification procedure:

Aquatic Chronic 3: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -

Printing: 23/10/2025

Date of compilation: 23/10/2025

Version: 1

Page 14/14